

ISGUS Terminal IT 4211 IT 4211 FP



IT 4211 and IT 4211 FP for Access Control

- » Status display and bookings acknowledgment via LED and acoustic signal
- » Door opening via integrated electronic relay or external door control (TSE 400) in the secured area
- » 2 inputs
- » Anti tamper alarm device via case contact
- » Connection to terminal IT 8xxx or ACM 40xx via network
- » Easy and flexible installation
- » Multi company feature for up to 10 different companies (IT 4211)

- » Terminals for access control with verification or identification mode (IT 4211 FP)
- » Two finger templates per person can be used for verification or identification (IT 4211 FP)
- » Combined with ZEUS® biometrics integration into any security concept (IT 4211 FP)
- » Recording of fingerprint data possible on IT 8200 FP terminal (IT 4211 FP)
- » Easy parameterisation via integrated web server

Technical Information

IT 4211 IT 4211 FP



IT 4211



IT 4211 FP



Badge reader systems

- » ISGUS-Prox
- » Hitag 1
- » LEGIC
- » Mifare
- » HID

Voltage

- » 24 V DC
- » PoE in accordance with IEEE 802.3af performance class 0

Current consumption

- » 2,23 W

Protection type

- » IP 65 (front side)

Protection class

- » III / EN 62368-1

Environment

- » Suited for indoor and outdoor environments
- » No direct sunlight
- » Ambient temperature: -10° C to +55° C

Rel. humidity

- » max. 85 % (non condensing)

Data communication

- » TCP/IP

Weight

- » Approx. 0,2 kg (IT 4211)
- » Approx. 0,25 kg (IT 4211 FP)

Dimensions

- | | |
|------------------|------------------|
| IT 4211 | IT 4211 FP |
| » Height: 114 mm | » Height: 155 mm |
| » Width: 75 mm | » Width: 75 mm |
| » Depth: 36 mm | » Depth: 60 mm |

